

10-3D-4 Bicycle Parking Standards

All uses which are subject to Site Design Review (see Section 10-4C-2) shall provide bicycle parking, in conformance with the following guidelines, which are evaluated during Site Design Review. Buildings that do not require site design review are encouraged to incorporate these standards.

A. Number of Bicycle Parking Spaces. Unless specified in 1-7 below, at least one bicycle parking space shall be supplied per 50 required vehicle parking spaces with a minimum of 2 spaces provided. Generally, a bike rack(s) would be installed that have the capacity to accommodate the required number of spaces. Providing sheltered spaces (under an eave, overhang, independent structure, or similar cover) is encouraged.

The following additional standards apply to specific types of development:

1. Multi-Family Residences.
Provide one bicycle parking space for every unit (structures with 4 or more units).
2. Parking Structures and Park & Ride Facilities.
All parking structures shall provide a minimum of one bicycle parking space for every 10 motor vehicle parking spaces.
3. Elementary and middle schools, both private and public.
Provide one bicycle parking space for every 10 students that the school is designed to accommodate.
4. High schools, both private and public.
Provide one bicycle parking space for every 20 students that the school is designed to accommodate.
5. Colleges and trade schools.
Provide one bicycle parking space for every 10 motor vehicle spaces plus one space for every dormitory unit.
6. Mixed Use Zones.
Within the M-1, M-2, and M-3 zones, individual businesses shall provide their own bicycle parking, or spaces may be clustered between businesses to serve up to six (6) bicycles. One bicycle parking space shall be provided per 25 required vehicle spaces with a minimum of 5 spaces provided. Bicycle parking spaces should be located in front of the businesses, either on the sidewalks or in specially constructed areas such as pedestrian curb extensions. Inverted "U" style racks are recommended. Bicycle parking shall not interfere with pedestrian passage, leaving a clear area of at least 36 inches between bicycles and other existing and potential obstructions.
7. Multiple Uses.
For buildings with multiple uses (such as a commercial or mixed use center), bicycle parking standards shall be calculated by using the total number of motor vehicle parking spaces required for the entire development. One bicycle parking space per 25 motor vehicle parking spaces is recommended, with a minimum of 5 spaces.

B. Exemptions. This section does not apply to single family, two-family, and three-family housing (attached, detached or manufactured housing), home occupations, accessory dwelling units, or other developments with fewer than 10 required vehicle parking spaces.

C. Location and Design. Bicycle parking shall be conveniently located with respect to both the street right-of-way and at least one building entrance (e.g., no farther away than the closest parking space). It should be incorporated whenever possible into building design and coordinated with the design of street furniture when it is provided. Street furniture includes benches, street lights, planters, and other pedestrian amenities.

- D. Visibility and Security. Bicycle parking shall be visible to cyclists from street sidewalks or building entrances, so that it provides sufficient security from theft and damage.
- E. Options for Storage. Bicycle parking requirements for long-term and employee parking can be met by providing a bicycle storage room, bicycle lockers, racks, or other secure storage space inside or outside of the building.
- F. Lighting. Bicycle parking shall be at least as well lit as vehicle parking for security.
- G. Reserved Areas. Areas set aside for bicycle parking shall be clearly marked and reserved for bicycle parking only.
- H. Hazards. Bicycle parking shall not impede or create a hazard to pedestrians. Parking areas shall be located so as to not conflict with vision clearance standards (Section 10-3B-2, subsection N).

10-3D-5 Loading Space Standards

It is the intent of this section to require all future commercial, business, institutional, or industrial development to provide off-street loading facilities in order to guarantee full utilization of existing rights of way to accommodate present and future traffic demands. Off-street loading facilities are intended to provide adequate space to accommodate outside deliveries from large vehicles which cannot be functionally served by normal parking stalls. Off-street loading facilities must be located in such a manner that service vehicles do not block or intrude into public rights of way or block driveways or parking area circulation.

A. Location and Design.

1. All off-street loading spaces shall be designed to minimize impacts on adjacent properties.
2. In all cases, loading facilities shall be located on the same lot as the structure they are designed to serve. Required yards cannot be used for loading. Off-street loading space shall not be included in an area used to satisfy off-street parking requirements.
3. Loading spaces shall be designed and located so vehicles using these spaces do not project into any public right-of-way or otherwise extend beyond property lines.
4. Loading spaces shall be designed and built so no vehicles are required to back to or from an adjacent street, except for minor access for heavy trucking in industrial zones on local access streets.
5. When a proposed structure is intended to be used concurrently for different purposes, final determination of required loading spaces shall be made by the Director, provided the loading requirement for the combined uses shall not be less than the total requirement for each separate use.

B. Required Off-Street Loading Spaces. The minimum number of off-street loading spaces shall be required according to the following table, unless the number is reduced by the Director.